Mount Vernon Boom Lift License

Marysville Boom Lift License - Only completely qualified individuals should operate an aerial boom lift. Qualification can be obtained through a combination of classroom sessions and practical training with the particular kind of aerial lift which will be used on the job. A License is required for any person who operates or works on an aerial boom lift.

Vehicle-mounted aerial devices consist of the following work vehicles: extensible boom platforms, aerial ladders, articulating boom platforms, vertical towers, and whichever combination of these kinds.

When making use of a boom lift, there are several basic safety regulations which apply to all boom lifts. Safety of the worker is a main concern whilst they are working inside the basket. The worker must at all times wear a body harness and lanyard, connecting it to the boom or basket. Never tie off to an equipment, an adjacent pole or a structure. Staff must stand on the floor of the basket, and never sit or climb on the basket edge. The manufacturer's load restrictions must be adhered to.

Aerial lift operators should be authorized to make use of the machines. The operator has to know all the aspects of the device and should have access to the manufacturers guidebook which must be kept within the lift. Operators are responsible for ensuring that safety procedures are followed in the operation of the lift. Testing lift controls on a daily basis must be performed. Set brakes and position outriggers (if they are utilized) on a stable surface or on pads. When working on a slope, utilize wheel chocks.

Never move an aerial lift truck with an elevated boom while workers are within the basket. Extensible boom platforms and articulating boom made use of as personnel carriers should have accessible, plainly marked, upper controls. Except in emergency circumstances, lower controls must not be utilized to override upper controls unless the person inside the lift gives authorization.

Do not wear tree or pole climbers shall whilst working from an aerial lift.
The insulated part of the aerial lift must not be altered.
Make certain that the booms are thoroughly checked, that the machine is properly cradled and the outriggers are in the stowed position before moving.
When operating a boom lift next to power lines, ensure the lines are di-electrically tested according to local rules.