

## Mount Vernon Loader Ticket

Marysville Loader Ticket - Gehl articulated loaders have been made to fit just about any condition. They provide great traction and optimal maneuverability due to a heavy-duty oscillating joint which offers 45-degree rotating angles right and left, together with 10 degrees of oscillating in both directions. Access is granted to tight and confined spaces by narrow machine widths. Most skid-steer loaders with equivalent operating capacities are unable to compete. The bucket and tires on the Gehl machine follow a constant turn radius also. This means the rear tires of the loader follow the trail of the front tires.

The articulated loaders features hydraulic power and precision that come with all the Gehl equipment. Bucket float and lift arm features permit these equipment to do light scraping and rearward leveling actions. Flat-face couplers, with the two easily accessible auxiliary hydraulic lines power several instruments and make changing the attachments a simple task to perform.

Gehl articulated loaders have distinctively designed lift arms which are made in order to achieve maximum strength, fast cycle times and great visibility. The specialized linkage design makes it possible for mechanized self-leveling action in both the up and down directions. It could also easily execute excellent bucket dump angles at the top and mid ranges of the hoist path as well as providing excellent forward reach. Models 140 and 340 have parallel type linkage and the model 540 has "Z" bar type linkage. These linkage patterns offer great bucket breakout forces from two thousand four hundred thirty three pounds on the 140 model to 10,749lbs on the model 540.

Gehl articulated loaders are known all over the globe for their ease of operation, supreme ergonomics and unsurpassed visibility. The 540 and 340 machines have a total cab enclosure option obtainable. This offers better safety and comfort for the operator. Secure operation and 360 degree visibility is sustained by placing the operator higher than the load to ensure an excellent viewpoint of the attachment. An inching pedal allows the operator to alter ground speed whilst maintaining a fixed engine velocity. This feature allows the individual operating it to properly run attachments while making sure precise machine velocity control. A multi-function joystick controls the float, differential lock and auxiliary hydraulic functions, bucket, travel direction as well as the lift arm.